



**TECHNICAL DATA SHEET**

|                |                             |
|----------------|-----------------------------|
| PRODUCT        | <b>INSTABEX BZ</b>          |
| TDS Number     | QA/FPS/0064                 |
| Date of Issue  | 25 <sup>th</sup> June, 2005 |
| Version Number | 04                          |

**INSTABEX BZ**

**PRODUCT DESCRIPTION**

The **INSTABEX BZ** series is based on Barium-Zinc complex and is the most suitable for topcoats of ALC to be exported to European countries. Perfect balance of Barium & Zinc assures better heat stability but also better weather ability. Barium-Zinc complex ensures sulfide stain resistance. Incorporation of Epoxy oil imparts synergistic action.

| <b>Properties</b>                        | <b>Test Methods</b> | <b>Specification</b> |
|--|---------------------|----------------------|
| Appearance                               | VISUAL              | Clear Liquid         |
| Color ( Gardner unit)                    | QA/TMM/005          | 4 max                |
| Specific Gravity at 30°C                 | QA/TMM/010          | 0.90 ± 0.03          |
| Viscosity (Ford Cup B4) at 30°C, Seconds | QA/TMM/006          | 20 max               |

For more information please call (91-22) 5591-2881 or email [aryavart@vsnl.com](mailto:aryavart@vsnl.com)

Typical values are representative of production and may vary from time to time. All information to the best of our knowledge and belief is accurate and reliable as on the date of compilation. Moreover no warranty or guarantee is made as to the accuracy, reliability or completeness nor do we offer any warrant against patent infringement. It is the users responsibility to ascertain the suitability of this information for his or her use. Sampling and Testing procedures in effect at the time of production will be used for certification and we reserve the right to use any test method in certifying the material.