



**TECHNICAL DATA SHEET**

PRODUCT	<b>INSTABEX C – 2</b>
TDS Number	QA/FPS/008
Date of Issue	1 <sup>st</sup> September, 2005
Version Number	01

**INSTABEX C – 2**

**PRODUCT DESCRIPTION**

The following ranges of products are essentially stabilizer one-packs where external as well as internal lubricants are to be added separately. This gives maneuverability to the operator to adjust the formulation in relation to filler loading.

This is the perfect stab one pack system for local conditions. It is highly recommended for twin screw extruders but can also be used on single screw extruders.

<b>Properties</b>	<b>Test Methods</b>	<b>Specification</b>
Appearance	QA/TMM/026	Fine Off White Powder
Metal Content as % Pb	QA/TMM/014	50.00 to 52.00
Metal Content as % PbO	QA/TMM/014	53.86 to 56.01
% Partical Size	QA/TMM/011	99.00 Through 200 Mesh
Specific Gravity	QA/TMM/010	2.00 to 2.30
%Moisture Content	QA/TMM/009	1.00 Max.

For more information please call (91-22) 5591-2881 or email [aryavart@vsnl.com](mailto:aryavart@vsnl.com)

Typical values are representative of production and may vary from time to time. All information to the best of our knowledge and belief is accurate and reliable as on the date of compilation. Moreover no warranty or guarantee is made as to the accuracy, reliability or completeness nor do we offer any warrant against patent infringement. It is the users responsibility to ascertain the suitability of this information for his or her use. Sampling and Testing procedures in effect at the time of production will be used for certification and we reserve the right to use any test method in certifying the material.