



TECHNICAL DATA SHEET

PRODUCT	INSTABEX KC
TDS Number	QA/RMS/0158
Date of Issue	25 th May, 2005
Version Number	04

INSTABEX KC

PRODUCT DESCRIPTION

The **INSTABEX KC** series kickers are an alternative kicker system based on Potassium-Zinc. These systems are free from heavy metals and hence fulfill requirements of export to European countries. These products not only reduce the decomposition temp. of blowing agent but provide adequate thermal stability also.

Properties	Test Methods	Specification
Appearance	VISUAL	Clear liquid
Color (Gardner unit)	QA/TMM/005	NA
Specific Gravity at 30°C	QA/TMM/010	0.90 ± 0.03
Viscosity (Ford Cup B4) at 30°C, Seconds	QA/TMM/006	30 Max.
MTO Tolerance	QA/TMM/024	1:19

For more information please call (91-22) 5591-2881 or email aryavart@vsnl.com

Typical values are representative of production and may vary from time to time. All information to the best of our knowledge and belief is accurate and reliable as on the date of compilation. Moreover no warranty or guarantee is made as to the accuracy, reliability or completeness nor do we offer any warrant against patent infringement. It is the users responsibility to ascertain the suitability of this information for his or her use. Sampling and Testing procedures in effect at the time of production will be used for certification and we reserve the right to use any test method in certifying the material.