



## TECHNICAL DATA SHEET

PRODUCT	<b>INSTABEX MT 1080</b>
TDS Number	QA/FPS/0012
Date of Issue	1 <sup>st</sup> Oct 2005
Version Number	01

### INSTABEX MT-1080 (Tin Stabilizer)

#### PRODUCT DESCRIPTION

This is a Tin Mercaptide and has excellent heat stability. It gives crystal clarity and high gloss to the finished products when properly formulated. **INSTABEX MT-1080** has been carefully formulated to give optimum performance can be used in all types of PVC processing methods like flexible extrusions, injection moulding etc. Inclusion of suitable light stabilizers like Tinuvin 320 will impart good weather ability to the finished goods.

#### HANDLING AND STORAGE

MT-1080 is a liquid tin mercaptide heat stabilizer and should be handled with normal precautions used in good industrial practices for organic liquids. Store in cool and dry place. Indoor storage is recommended. Stainless steel is recommended for piping, valves and pumps used to handle MT-1080. Do not use iron.

Properties	Test Methods	Specification
Appearance	Visual	Clear Liquid
Color	Gardner Scale	Less than 1
Specific Gravity @ 25°C		1.18 ± 0.03
Tin Content		12.00 ± 0.50%

For more information please call (91-22) 5591-2881 or email [aryavart@vsnl.com](mailto:aryavart@vsnl.com)

Typical values are representative of production and may vary from time to time. All information to the best of our knowledge and belief is accurate and reliable as on the date of compilation. Moreover no warranty or guarantee is made as to the accuracy, reliability or completeness nor do we offer any warrant against patent infringement. It is the users responsibility to ascertain the suitability of this information for his or her use. Sampling and Testing procedures in effect at the time of production will be used for certification and we reserve the right to use any test method in certifying the material.