



TECHNICAL DATA SHEET

PRODUCT	ZINC OCTOATE 12%
TDS Number	QA/FPS/0111
Date of Issue	25 th June, 2005
Version Number	04

ZINC OCTOATE 12%

PRODUCT DESCRIPTION

Zinc is an auxiliary drier, used in conjunction with redoxmetals. The primary function of the Zinc is to keep the film "open" by retarding surface dry, thus permitting hardening throughout and preventing surface wrinkling.

Zinc is a powerful wetting and dispersing agent and when incorporated early in the formulation, greatly reduces the time of mixing and grinding. Extremely low color of **ARYADRY ZINC** facilitates Zinc addition without discoloration of film.

ARYADRY ZINC is available as a solution in MTO in various concentrations.

Properties	Test Methods	Specification
Appearance	VISUAL	Clear liquid
Color (Gardner unit)	QA/TMM/005	4
Specific Gravity at 30°C	QA/TMM/010	0.95 ± 0.03
Viscosity (Ford Cup B4) at 30°C, Seconds	QA/TMM/006	30 max
Non-volatile matters at 120°C 1hr, % w/w	QA/TMM/013	NA
Metal content as % Zn	QA/TMM/026	12.0 ± 0.2
MTO Tolerance	QA/TMM/024	1:19

For more information please call (91-22) 5591-2881 or email aryavart@vsnl.com

Typical values are representative of production and may vary from time to time. All information to the best of our knowledge and belief is accurate and reliable as on the date of compilation. Moreover no warranty or guarantee is made as to the accuracy, reliability or completeness nor do we offer any warrant against patent infringement. It is the users responsibility to ascertain the suitability of this information for his or her use. Sampling and Testing procedures in effect at the time of production will be used for certification and we reserve the right to use any test method in certifying the material.